

주요 사양:  
 (@Ta=25℃)

| 부품 번호   | V <sub>OFF</sub><br>(최소) | I <sub>ON</sub><br>(최대) | R <sub>ON</sub><br>(typ.) | C <sub>OFF</sub><br>(typ.) | C(pF)xR(Ω)<br>(typ.) | I <sub>OFF</sub><br>(최대) | t <sub>ON</sub><br>(최대) | t <sub>OFF</sub><br>(최대) |
|---------|--------------------------|-------------------------|---------------------------|----------------------------|----------------------|--------------------------|-------------------------|--------------------------|
| TLP3419 | 80V                      | 200mA                   | 6Ω                        | 6.5pF                      | 39                   | 1nA                      | 0.4ms                   | 0.4ms                    |
| TLP3451 | 60V                      | 120mA                   | 10Ω                       | 0.7pF                      | 7                    | 1nA                      | 0.2ms                   | 0.2ms                    |
| TLP3441 | 40V                      | 140mA                   | 7Ω                        | 0.7pF                      | 4.9                  | 1nA                      | 0.2ms                   | 0.2ms                    |
| TLP3442 | 40V                      | 100mA                   | 15Ω                       | 0.3pF                      | 4.5                  | 1nA                      | 0.2ms                   | 0.2ms                    |
| TLP3431 | 20V                      | 450mA                   | 0.8Ω                      | 5.0pF                      | 4                    | 1nA                      | 0.5ms                   | 0.5ms                    |
| TLP3450 | 20V                      | 200mA                   | 3Ω                        | 0.8pF                      | 2.4                  | 1nA                      | 0.2ms                   | 0.2ms                    |